HAFELE from



Individual Components

	Description	Material	Finish/Color	Length	Qty.	Item No.
	Double roller running gear	Wheels: Nylon	-	-	2 pcs.	941.20.012
	Suspension bolt with bolt, M12	_	_	_	2 pcs.	941.20.025
	Track stopper with adjustable retention spring	_	_	_	2 pcs.	941.20.041
Ì	Wall buffer	Rubber	black	-	1 pc.	940.40.051
2: N	Locking wrench to suspension plate	Steel	_	_	1 pc.	941.20.091
9	Lower guide channel, 20 x 20 x 3 (13/16" x 13/16" x 1/8")	Aluminum	anodized	6 m (19' 8 1/4")	-	941.00.960
				2.5 m (8' 2 7/16")	-	941.00.925
Ť	Lower guide	Aluminum	anodized	_	-	980.84.033
	Glass suspension profile	Aluminum	unanodized	6.5 m (21' 3 15/16")	-	946.10.650
	Cover cap, suspension	Plastic	black	-	-	946.11.310
	Cover cap, glass suspension	Plastic	black	_	-	946.11.320
	Glass fixing parts, 10 (3/8"), set for 1 door includes eccentric cam and centering wedges	-	_	_	_	946.20.010
	Glass fixing parts, 12.7 (1/2"), set for 1 door includes eccentric cam and centering wedges	_	_	_	_	946.20.013
~	Wrench, open-ended, to adjust eccentric cam	Steel	_	_	_	946.20.000
	Upper tracks, pre-drilled	Aluminum	anodized, clear	3 m (9' 10 1/8")	_	941.20.300
·				4 m (13' 1 1/2")	-	941.20.400
				6 m (19' 8 1/4")	_	941.20.600

Note

Item numbers are valid for only 1 piece, when ordering individual components please state the desired amount. For 2 bi-parting sliding glass order 2 sets.

8				
	HAWA angle profile	Page 1.287		
	HAWA assembly wedge	Page 1.288		
	Floor mounted door stop	Page 1.204		
	Glass suspension profile and glazing components	Page 1.297		
	Locks	Pages 1.294-1.295		
	Lower guides and lower guide channel	Page 1.298		
	Finishes	Page 1.296		

Dimensions in mm Inches are approximate 1