











### Set

	Item No.
For 1 wood door	404.95.001
For 1 glass door	404.95.010

### Set Components

Description	Color	Qty. for 1 wood door	Qty. for 1 glass door
 Running gear, four plastic-coated ball bearing wheels	–	2 pcs.	2 pcs.
 Carrier profile with M7 suspension bolt	–	2 pcs.	–
 Cover caps, 20 x 25 (3/16" x 1 3/8")	gray	2 pcs.	–
 Patch suspension	–	–	2 pcs.
 Suspension bolt, M7, including mounting screws	–	–	1 pc.
Hex Key, 4 mm (5/32")	–	1 pc.	–

### Individual Components

Description	Material	Finish	Length	Item No.
 Single upper track, pre-drilled 36 x 33 (1 7/16" x 1 5/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	404.99.925
			3.5 m (11' 5 13/16")	404.99.935
 Dual upper track, pre-drilled 36 x 63 (1 7/16" x 2 1/2")	Aluminum	anodized	2.5 m (8' 2 7/16")	404.96.925
			3.5 m (11' 5 13/16")	404.96.935
 Single lower guide channel, clip-on or glue-on, 4.5 x 35 (3/16" x 1 3/8")	Aluminum	anodized	2.5 m (8' 2 7/16")	404.98.925
			3.5 m (11' 5 13/16")	404.98.935
 Dual lower guide channel, clip-on or glue-on, 4.5 x 54 (3/16" x 2 1/8")	Aluminum	anodized	2.5 m (8' 2 7/16")	404.97.925
			3.5 m (11' 5 13/16")	404.97.935
 Fixing set to dual lower guide channel, includes 5 pcs. (2 pcs. per meter)	–	–	–	404.97.990

Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm  
Inches are approximate