









Set

	Item No.
	941.00.007










Set Components

	Description	Material	Color/Finish	Qty.	Item No.
	Double roller running gear	-	-	2 pcs.	941.00.015
	Suspension bolt, M8 x 32	Steel	zinc-plated	2 pcs.	940.54.021
	Set nut, M8	Steel	zinc-plated	2 pcs.	940.54.022
	Clamp shoe adjustable from 6 - 12.7 (1/4" - 1/2")	Aluminum	mill finish	2 pcs.	941.00.020
	Track stopper, with adjustable retention spring	Plastic	gray	1 pc.	940.60.043
	Track stopper	Plastic	gray	1 pc.	940.60.041
	Floor guide, adjustable from 6 - 12.7 (1/4" - 1/2")	-	-	1 pc.	941.00.031
	Buffer	Rubber	black	1 pc.	940.60.051

Note

Item numbers are valid for only 1 piece, when ordering individual components please state the desired amount. For 2 bi-parting sliding glass doors please order 2 sets.

Individual Components

	Description	Material	Color/Finish	Length	Item No.
	Upper Tracks, pre-drilled, 95 x 62 (3 47/64" x 2 7/16")	Aluminum	unanodized	2.5 m (8' 2 7/16")	941.00.254
	Upper Tracks, pre-drilled, 95 x 62 (3 47/64" x 2 7/16")			6 m (19' 8 1/4")	941.00.604
	Clip-on Fascia to upper track, 94.5 x 9 (3 23/32" x 23/64")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.00.825
	Clip-on Fascia to upper track, 94.5 x 9 (3 23/32" x 23/64")			6 m (19' 8 1/4")	941.00.860
	Support Profile for Fixed Glass, pre-drilled, 53 x 19 (2 3/32" x 3/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.01.825
	Support Profile for Fixed Glass, pre-drilled, 53 x 19 (2 3/32" x 3/4")			6 m (19' 8 1/4")	941.01.860
	Fixed Glazing Profile/Lower Guide Channel, pre-drilled, 30 x 20 (1 3/16" x 25/32")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.01.725
	Fixed Glazing Profile/Lower Guide Channel, pre-drilled, 30 x 20 (1 3/16" x 25/32")			6 m (19' 8 1/4")	941.01.760
	Fixing set for support profile and fixed glazing profile	-	-	-	941.01.899
	End piece to fascia, one-sided, wall mounted	Aluminum	anodized	64 mm (2 33/64")	941.00.068
	End piece to fascia, one-sided, wall mounted			70 mm (2 3/4")	941.00.069
	Sealing profile for 8 and 10 (5/16" and 3/8") glass	Rubber	black	20 m (65' 7 7/16")	941.00.103
	Seal	Plastic	black	20 m (65' 7 7/16")	941.00.094
	Soft closer 10 - 60 kg (22 - 132 lbs.)	-	-	-	940.60.045
	Soft closer 61 - 100 kg (135 - 220 lbs.)				940.60.010
	Cover cap for soft closer				940.60.094

Note

Mounting instructions (included in fitting set) for planning and execution available upon request.

Floor mounted door stop

Page 1.204

HAWA-Toplock

Pages 1.289-1.293

Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm
Inches are approximate