

Silent Aluflex 40 Accessories

	Description	Material	Finish/Color	Length	Item No.
	Mullion	Aluminum	silver colored anodized (E6/EV1)	2 m (6' 6 3/4")	403.37.922
				3 m (9' 10 1/8")	403.37.923
				6.05 m (19' 10 3/16")	403.37.926
	Mounting clips for the above mullion	Plastic	white	-	403.35.300
	Decorative mullion, self adhesive for optical subdividing of the door panels	Aluminum	-	2 m (6' 6 3/4")	403.53.920
				3 m (9' 10 1/8")	403.53.930
				6 m (19' 8 1/4")	403.53.960
	Gasket, for panel thicknesses 4 – 5 (3/16")	Plastic	transparent	2 m (6' 6 3/4")	403.36.985
	End bracket for all guide tracks, for covering the sides, screw-mounted	Steel	powder-coated white aluminum RAL 9006	-	403.55.991
	Center door stopper for mounting into the top guide track	Plastic	gray	-	403.50.945
	Cover cap, for single running bottom track	Stainless steel	brushed	-	403.55.060
	Wall mounting bracket, for top guide track, required every 500 mm (19 11/16")	Steel	white aluminum RAL9006	-	403.55.980
	Soft and self closing mechanism, for door weights up to 15 kg (33 lbs.)		black/gray		403.50.988
	Soft and self closing mechanism, for door weights up to 40 kg (88 lbs.)	Plastic	black/green	-	403.50.999
	Note Minimum door width with one soft and self closing mechanism is 500 (19 5/8"), with two, 830 (36 5/8")				
	Wall compensating profile	Aluminum	silver colored anodized	3 m (9' 10 1/8")	940.93.230
	Wall connection profile	Aluminum	silver colored anodized	6 m (19' 8 1/4")	403.65.960

Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm
Inches are approximate