











**Set**

- For bi-parting sliding doors without upper track and lower guide channel

| Item No.   |
|------------|
| 940.81.009 |





**Set Components**

|                                                                                     | Description                                                | Material | Color                      | Qty.   | Item No.   |
|-------------------------------------------------------------------------------------|------------------------------------------------------------|----------|----------------------------|--------|------------|
|    | Double roller running gear                                 | -        | -                          | 4 pcs. | 940.80.012 |
|    | Two-way suspension plate<br>M10 bolt and mounting screws   | Aluminum | silver colored<br>anodized | 4 pcs. | 940.80.022 |
|    | Floor mounted guide, rattle-free                           | -        | -                          | 2 pcs. | 940.40.031 |
|    | Track stopper with adjustable<br>retention spring          | -        | -                          | 1 pc.  | 940.80.041 |
|    | Height adjusting pin                                       | Steel    | -                          | 1 pc.  | 940.40.091 |
|    | Deflection roller with end stops                           | -        | -                          | 2 pcs. | 940.80.086 |
|    | Clamping element for fastening<br>ends of the toothed belt | -        | -                          | 1 pc.  | 947.00.055 |
|   | Clamping element for fastening<br>continuous toothed belt  | -        | -                          | 1 pc.  | 947.00.056 |
|  | Toothed belt, glass-fiber reinforced<br>10 m (32" 11/16")  | -        | black                      | 1 pc.  | 947.00.037 |
|  | Door stop, screw-on                                        | Rubber   | gray                       | 2 pcs. | 940.40.051 |

**Note**

Item numbers are valid only for 1 piece, when ordering individual components, please state the desired amount  
The toothed belt (length 10 m) is calculated for 2 sliding doors having a maximum width of 1200 mm (3' 11 1/4") each

**Individual Components**

|                                                                                     | Description                  | Material | Finish/Color           | Length             | Item No.   |
|-------------------------------------------------------------------------------------|------------------------------|----------|------------------------|--------------------|------------|
|  | Upper tracks,<br>pre-drilled | Aluminum | clear<br>anodized      | 1.4 m (4' 7 1/8")  | 940.80.140 |
|                                                                                     |                              |          |                        | 1.6 m (5' 3")      | 940.80.160 |
|                                                                                     |                              |          |                        | 1.8 m (5' 10 7/8") | 940.80.180 |
|                                                                                     |                              |          |                        | 2 m (6' 6 3/4")    | 940.80.200 |
|                                                                                     |                              |          |                        | 2.2 m (7' 2 5/8")  | 940.80.220 |
|                                                                                     |                              |          |                        | 2.5 m (8' 2 7/16") | 940.80.250 |
|                                                                                     |                              |          |                        | 3 m (9' 10 1/8")   | 940.80.300 |
|                                                                                     |                              |          |                        | 4 m (13' 1 1/2")   | 940.80.400 |
| 6 m (19' 8 1/4")                                                                    | 940.80.600                   |          |                        |                    |            |
|  | Guide rail                   | Plastic  | black                  | 1.3 m (4' 3 1/8")  | 940.41.130 |
|  | Cover cap                    | Plastic  | anthracite             | -                  | 940.80.060 |
|  | Door stop, floor mounted     | -        | chrome-plated,<br>matt | -                  | 940.40.052 |

|                    |                   |
|--------------------|-------------------|
| Confort guides     | Page 1.160        |
| HAWA angle profile | Page 1.157        |
| Futura framing kit | Pages 1.153-1.155 |

Calculating the upper  
track length (L):  
L = CO x 2 + 120 mm  
(4 3/4")  
CO = Clear opening

Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm  
Inches are approximate