1

Set

• For 1 sliding door without the upper running tracks

Item No.
941.00.115

moving hardware forward

Nare

Set Components

	Description	Material	Color/Finish	Qty.
CTO .	Running gear, with four wheels	Plastic	white	2 pcs.
	Suspension bolt, M8 x 35 mm	Steel	zinc-plated	2 pcs.
A REPORTED	Carrier block	Plastic	white	2 pcs.
	Suspension profile for carrier block	Aluminum	unanodized	2 pcs.
	Door stopper with adjustable retention spring	Plastic	gray	2 pcs.
	Lower guide	Plastic	anthracite gray	1 pc.
と	Fixing screws	-	-	1 set

Individual Components

	Description	Material	Color/Finish	Length	Item No.
	Dual upper running track	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.926
				3.5 m (11' 5 13/16")	941.13.936
				6 m (19' 8 1/4")	941.13.961
	Single upper running track, 30 x 31 (1 3/16" x 1 1/4")	Aluminum	unanodized	2 m (6' 6 3/4")	941.00.200
				2.5 m (8' 2 7/16")	941.00.250
				6 m (19' 8 1/4")	941.00.600
	Dual upper running track, 73 x 31 (2 7/8" x 1 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.925
				3.5 m (11' 5 13/16")	941.12.935
				6 m (19' 8 1/4")	941.12.960
	Triple upper running track, 111 x 31 (4 3/8" x 1 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.425
				3.5 m (11' 5 13/16")	941.13.435
				6 m (19' 8 1/4")	941.13.460
	Clip profile, with notch, for wooden doors (Only used in combination with 940.93.325 and 940.93.330)	Aluminum	anodized	3 m (9' 10 1/8")	941.12.431
	Vertical handle profile	Aluminum	silver -	2.5 m (8' 2 7/16")	940.93.325
				3 m (9' 10 1/8")	940.93.330
	Safety clip				
	Note Only required in conjunction with vertical handle profile	Aluminum	silver	-	940.92.090
	Track cleaning tool	Aluminum	silver	-	941.00.099
	Soft Closer				940.60.010
	Cover cap, for soft closer				940.60.094
	Drill jig, for soft closer				940.60.095

Installation Plan

(Included in fitting set), mounting instructions for planning and execution available upon request.

Dimensional data not binding. We reserve the right to alter specifications without notice.