Set

• For a single sliding door without running track

| ion Door width | | Item No. |
|---|--------------------------------|------------|
| A, without Soft Close mechanism | - | 940.42.005 |
| B, with Soft Close on one side | ≥592 (23 5/16") | 940.43.000 |
| C, with Soft Close on both sides (twin mechanism) | 727 – 846 (28 5/8" – 33 5/16") | 940.43.009 |
| D, with Soft Close on both sides (double mechanism) | 847 – 966 (33 3/8" – 38") | 940.43.005 |
| E, with two Soft Close for both sides | ≥916 (36") | 940.43.008 |

ware

Note

Version A includes only one track stopper, please order further track stoppers separately, if required. For 2 bi-parting and bypassing sliding doors, please order 2 sets.

Set Components

| | Description | Material | Finish/Color | For Version | Qty. | ltem No. |
|----------------|---|--|--------------|---------------------|------------|------------|
| <u>A</u> | Running gear, suspension screw with nut, | Steel galvanized | galvanized | А | 2 pcs. | 940.42.013 |
| Carl And | support flange for screw-mounting, Steel galvanized without soft and self-closing mechanism | | gaivanizeu | В | 1 pc. | 940.42.013 |
| | Running gear, suspension screw with nut, support flange for screw-mounting, Steel galvanized soft and self-closing mechanism on one side | Ohaal | | В | 1 pc. | 040 40 017 |
| | | gaivanized | E | 2 pcs. | 940.42.017 | |
| i i | Running gear, suspension screws with nut, support flanges for screw-mounting, soft and self-closing mechanism on both sides (twin mechanism) | s for screw-mounting, losing mechanism on both sides Steel galvanized | | С | 1 pc. | 940.43.012 |
| Salaria in the | Running gear, suspension screws with nut, support flanges for screw-mounting, soft and self-closing mechanism on both sides (double mechanism) | Steel | galvanized | D | 1 pc. | 940.42.016 |
| | Floor guide | Plastic | gray | A, B, C, D and E | 1 pc. | 940.42.031 |
| | Track stopper with retaining spring and rubber bumper | Plastic | gray | A and B | 1 pc. | 940.42.040 |
| | Release device with stopper | Steel | galvanized | В | 1 pc. | 940.42.042 |
| | | | | C, D and E | 2 pcs. | 070.72.072 |

Note

Item numbers are valid only for one piece, when ordering individual components, please state the desired amount

Individual Components

| | Description | For door weight | For Version | Material | Finish | Length | Item No. | |
|--|--|--------------------------------|---------------------|----------|-------------------|--------------------|------------------|------------|
| | Single upper track, | 40 – 100 kg (88 – 220 lbs.) | | | mill | 2 m (6' 6 3/4") | 940.43.921 | |
| | | | | | | 2.5 m (8' 2 7/16") | 940.43.926 | |
| | | | | | | 3 m (9' 10 1/8") | 940.43.931 | |
| | pre-drilled, (W x H) 31 x 33 | | 0 | - | Aluminum | | 6 m (19' 8 1/4") | 940.43.961 |
| | (1 1/4" x 1 5/16") | | | | clear anodized | 2 m (6' 6 3/4") | 940.43.922 | |
| | | | | | | 3 m (9' 10 1/8") | 940.43.932 | |
| | | | | | | 6 m (19' 8 1/4") | 940.43.962 | |
| | Adjustable wall mounted guide (L x H) 64 x 68 (2 1/2" x 2 11/16") | _ | A, B, C, D and E | Steel | bronze | _ | 940.40.073 | |

Additional upper tracks, mounting Pages 1.50-1.53 options and accessories

Dimensions in mm Inches are approximate