



Fitting Set for widthwise mounting

- The dimensions listed are internal cabinet dimensions
- The cabinet and bed box constructions require a wood thickness of 20 mm

Material: Aluminum

| | |
|--|------------|
| | Item No. |
| | 271.95.204 |

Supplied With

- 1 pair foldaway fittings with pivot bearing and positioning bolt for gas pistons
- 2 Safety stops
- Safety lever with stop plate
- Mounting material
- Instructions

Note

It is essential for foldaway beds to be secured against tipping, according to EN 1129, (check the floor for suitability). Two safety stops are enclosed with every fitting set.



Retaining Straps for bedding

- With contact closing

| | |
|----------------------|------------|
| For mattress width | Item No. |
| up to 900 (35 7/16") | 271.87.920 |
| up to 1200 (47 1/4") | 271.87.921 |
| up to 1400 (55 1/8") | 271.87.922 |

Set Supplied With

- 3 male straps
- 3 female straps



| |
|--|
| For selecting the gas-loaded spring, the bed weight is needed. Bed box and slatted mattress frame + Mattress and bedding |
| = Bed weight |
| Mattress width + 2 x bed frame thickness + 125 mm |
| = internal cabinet height |
| Mattress length + 2 x bed frame thickness + 54 mm |
| = internal cabinet width |
| Gap on four sides between cabinet and front panel. |
| = minimum 4 mm |

The angular feet with mounting plate are screw-mounted to the foot side of the bed frame and to the inside of the front panel. A minimum 40 x 40 mm square beam is needed on four sides as slatted frame support.

Gas Pistons

- Pre-stressed with tightening strap
- Tightening strap needed to install or remove piston from fitting set

| | | |
|------------------|---------------|------------|
| Bed Weight | Pushing Force | Item No. |
| 40 kg (88 lbs.) | 400 N | 271.99.122 |
| 50 kg (110 lbs.) | 500 N | 271.99.140 |
| 60 kg (132 lbs.) | 600 N | 271.99.168 |
| 70 kg (154 lbs.) | 700 N | 271.99.186 |

Note

Order gas pistons separately depending on bed weight. 2 pcs. required per bed.



Angular Feet

- To support the opening bed
- When opening the bed, the angular feet must be extracted, turned by 90° and retracted to the stop

Material: Steel, powder-coated

| | |
|----------|------------|
| Finish | Item No. |
| aluminum | 271.95.361 |

Pair Supplied With

2 feet

Dimensional data not binding. We reserve the right to alter specifications without notice.

LGA quality certificate

- Detailed mounting instructions are enclosed with every fitting set
- Allows for the construction of foldaway beds according to your own plan

Dimensions in mm
Inches are approximate