HAFELE from



Sliding and Roller Shutter Systems Sliding Glass Door Fittings

Set

	Item No.
For 1 door with mounting instructions	405.02.007

Set Components

	Description	Material	Finish/Color	For 1 door
	Running gear, 4 rollers, with friction bearing, height adjustable ±1 mm (1/16")	Zinc	bright	2 pcs.
Common of the co	Top suspension screw, for connecting the running gear with the glass clamp shoe	Steel	galvanized	2 pcs.
	Top door stopper, with retaining spring	Plastic	gray	2 pcs.
	Guide with zero clearance, for screw-mounting, for 4 – 8 mm (3/16" – 5/16") thick glass	Zinc alloy	chrome-plated matt	1 pc.
000	Glass clamp shoe, for clamping to glass door	Zinc alloy	bright	2 pcs.

Individual Components

	Description	Min. cabinet top thickness	Material	Finish/Color	Length	Item No.
Flat Head	Single top running track, for screw-mounting under cabinet top	19 (3/4")	Aluminum	clear anodized	2.5 m (8' 2 7/16")	405.02.212
					3.5 m (11' 5 13/16")	405.02.213
Flat Head #7	Single top running track, for screw-mounting into groove	30 (1 3/16")	Aluminum	bright	2.5 m (8' 2 7/16")	405.00.202
					3.5 m (11' 5 13/16")	405.00.203
	Clip panel for clipping onto glass clamp shoe	-	Aluminum	clear anodized	2.5 m _(8' 2 7/16")	405.23.902
					3.5 m (11' 5 13/16")	405.23.935
	End caps and mounting clips, for clip panel	-	Plastic	anthracite	_	405.02.050
	Track end piece, for single top running track	-	Plastic	gray	-	405.00.070

Note

Dimensional data not binding. We reserve the right to alter specifications without notice.

1 set of end caps and mounting clips are required for a continuous clip panel, 2 sets are required for a divided clip panel. Please order glass fixing profile, running track and track end piece separately.

Flat head screws

Pages 11.137-11.138, 11.140

Dimensions in mm Inches are approximate