

RP 42/60

RP42 Complete Set

- For inset door thickness: 16 – 22 mm (5/8 – 7/8")
- Uses 35 mm hinges



Max. height of door	Min. height of door	Slide length	Item No.
1067 (42")	813 (32")	356 (14")	408.20.102
1067 (42")	813 (32")	406 (16")	408.20.111
1067 (42")	813 (32")	457 (18")	408.20.120
1067 (42")	813 (32")	508 (20")	408.20.139
1067 (42")	813 (32")	559 (22")	408.20.148
1067 (42")	813 (32")	610 (24")	408.20.157

- Supplied With**
- | | |
|-----------------------|---|
| 2 ball bearing slides | 2 racks |
| 1 profile rod 63" | 2 pivot rollers |
| 2 35 mm hinges | 8 slide screws (Pan head #8) |
| 2 mounting plates | 12 hinge and rack screws (Flat head #8) |
| 2 pinions | 4 hinge mounting plate screws (M4) |
| 4 saddles & bushings | 8 saddle & bushing screws (M4) |
| | 2 pivot roller screws (Raised flat head #6) |

Note

For thick doors 22 mm – 32 mm (7/8–1 1/4") use the 40 mm hinge, Item No. 329.05.632, and 40 mm mounting plate, Item No. 329.80.626. For overlay applications; Door thickness from 16 mm – 19 mm (5/8– 3/4"). Maximum overlay = 10 mm (3/8") use the 40 mm overlay hinge, Item No. 329.05.614, and 40 mm mounting plate, Item No. 329.80.626.

RP60 Complete Set

- For inset door thickness: 16 – 22 mm (5/8 – 7/8")
- Uses 35 mm hinges



Max. height of door	Min. height of door	Slide length	Item No.
1524 (60")	1067 (42")	356 (14")	408.20.200
1524 (60")	1067 (42")	406 (16")	408.20.219
1524 (60")	1067 (42")	457 (18")	408.20.228
1524 (60")	1067 (42")	508 (20")	408.20.237
1524 (60")	1067 (42")	559 (22")	408.20.246
1524 (60")	1067 (42")	610 (24")	408.20.255

- Supplied With**
- | | |
|-----------------------|---|
| 3 ball bearing slides | 2 racks |
| 1 profile rod 63" | 2 pivot rollers |
| 3 35 mm hinges | 12 slide screws (Pan head #8) |
| 3 mounting plates | 14 hinge and rack screws (Flat head #8) |
| 2 pinions | 6 hinge mounting plate screws (M4) |
| 6 saddles & bushings | 12 saddle & bushing screws (M4) |
| | 2 pivot roller screws (Raised flat head #6) |

Note

For thick doors 22 mm – 32 mm (7/8– 1 1/4") use the 40 mm hinge, Item No. 329.05.632, and 40 mm mounting plate, Item No. 329.80.626. For overlay applications; Door thickness from 16 mm – 19 mm (5/8– 3/4"). Maximum overlay = 10 mm (3/8") use the 40 mm overlay hinge, Item No. 329.05.614, and 40 mm mounting plate, Item No. 329.80.626.

Dimensional data not binding. We reserve the right to alter specifications without notice.