


Individual Components

	Description	Material	Finish/Color	Length	Item No.
	 Single running gear, with ball bearing nylon wheel and mounting bracket, 14 kg	Steel	galvanized	–	407.13.906
	 Double running gear, with ball bearing nylon wheel and mounting bracket, 28 kg	Steel	galvanized	–	407.14.903
	 Bumper, screw-mounts to stud or jamb	Rubber	black	–	407.01.930
	Bumper, plug-fit type	Rubber	white	–	406.24.100
	Guide, screw-mounted, recessed into cabinet bottom, maximum door weight: 40 kg (88 lbs.), groove size: 6 x 12 mm (1/4" x 1/2")	Plastic	natural	–	407.01.942
	Double guide, screw-mounted, floor-mounted, no groove required, maximum door weight: 40 kg (88 lbs.), adjustable from 19 - 35 mm (3/4" x 1 3/8") door width	Plastic	natural	–	407.01.951
	Single guide, screw-mounted, two-part guide (order 2 pcs. per door), floor-mounted, no groove required, guides have to be field-cut to fit door thickness, maximum door weight: 40 kg (88 lbs.)	Plastic	natural	–	407.01.960
	 Single upper track, pre-drilled	Aluminum	bright	2.5 m (8' 2 7/16")	407.10.042
				3.5 m (11' 5 13/16")	407.10.043
	 Double upper track, pre-drilled	Aluminum	bright	2.5 m (8' 2 7/16")	407.11.012
				3.5 m (11' 5 13/16")	407.11.013

Order specifications

Number of sliding doors
Type of upper track
Number of running gears
Door weight
Door stop

Special Application

	Description	Item No.
	Follower, for 3 or more bypassing doors	407.01.988

Supplied With

Spreading dowel
Buffer with fastening screw
Stop plate

Dimensional data not binding. We reserve the right to alter specifications without notice.