




Salice - Mounting Plates

• Depth adjustment with cam screw +2.8/-0.5 mm







Clip

- Screw-mounted
- Spring level
- With vertical adjustment (oblong holes)


Material: Steel; Finish: nickel-plated

Reinforcement	Model	Item No.
0	BAV3L09F	329.62.520
3	BAV3L39F	329.73.503
6	BAV3L69F	329.73.506

Material: Zinc; Finish: nickel-plated

Reinforcement	Model	Item No.
9	BAV3E99F	329.62.691
12	BAV3EC9F	329.85.012
18	BAV3EV9F	329.85.018





Clip

- Screw-mounted
- · Spring lever
- Pre-installed mounting screws
- 11 mm length for single-side mounting
- With vertical adjustment (oblong holes)

Material: Steel; Finish: nickel-plated


Reinforcement	Model	Item No.
0	BAVGL09F/16	329.73.510
3	BAVGL39F/16	329.85.043
6	BAVGL69F/16	329.73.516

• 7.5 mm length for single-side mounting

Material: Steel; Finish: nickel-plated

Reinforcement	Model	Item No.
0	BAVGL09F/20	329.73.520





ClipScrew-mounted in system holes

- Spring lever
- Pre-installed mounting screws
- 11 mm length for single-side mounting
- With vertical adjustment (oblong holes)

Material: Zinc die-cast; Finish: nickel-plated

Reinforcement	Model	Item No.
0	BAVGE09F/16	329.63.527
3	BAVGE39F/16	329.63.750
6	BAVGE69F/16	329.63.787
9	BAVGE99F/16	329.63.796
12	BAVGEC9F/16	329.85.032
18	BAVGEV9F/16	329.85.038

Dimensions in mm Inches are approximate

Raised head screws	page 11.145
--------------------	-------------