

Grass TIOMOS

- Soft close or self close
- A hinge system for all door applications
- 3 soft close settings, invisibly integrated in hinge arm
- Screw or dowel mounted
- 3-dimensional, continuous adjustment facility for door via eccentric (side adjustment) or special tech (depth and height adjustment):
Side adjustment ± 2 mm
Depth adjustment from $-2/+3$ mm
Height adjustment ± 2.5 mm depending on the mounting plate

Note

Dimensions in drawings and tables are calculated using factory settings and for mounting plate height 2 mm (3/32").

soft&silent)))

Opening angle: **110°**



Full Overlay Plus

- For large door overlay up to 24 mm

Material: Steel; Finish: nickel-plated

Version	Hinge Arm	Screw	Dowel
soft close		348.31.800	348.31.810
self close		348.31.600	348.31.610

Door Overlay	15	16	17	18	19	20	21	22*
0 baseplate				3	4	5	6	7
2 baseplate		3	4	5	6	7		

E - cup drilling distance

Note

Door overlay over 24 mm possible, with side adjustment by ± 2 mm.

Full Overlay Mounting

Material: Steel; Finish: nickel-plated

Version	Hinge Arm	Screw	Dowel
soft close		348.31.801	348.31.811
self close		348.31.601	348.31.611

Door Overlay	12	13	14	15	16	17	18	19
0 baseplate				3	4	5	6	7
2 baseplate		3	4	5	6	7		

E - cup drilling distance

Half Overlay/Twin Mounting

Material: Steel; Finish: nickel-plated

Version	Hinge Arm	Screw	Dowel
soft close		348.31.802	348.31.812
self close		348.31.602	348.31.612

Door Overlay	5.5	6.5	7.5	8.5	9.5	10.5	11.5	12.5
0 baseplate				3	4	5	6	7
2 baseplate		3	4	5	6	7		

E - cup drilling distance

Inset Mounting


Material: Steel; Finish: nickel-plated

Version	Hinge Arm	Screw	Dowel
soft close		348.31.803	348.31.813
self close		348.31.603	348.31.613


Door Overlay	-4	-3	-2	-1	0
0 baseplate				3	4
2 baseplate		3	4	5	6

E - cup drilling distance


Dowel mounted




Full overlay plus




Screw mount



Full overlay



Half overlay



Inset

