

Salice


- Quiet door/drawer closure
- As the door/drawer opens, pressure is then released allowing the adapter to move forward to receive the door/drawer again
- Use with hinges on pages **9.16–9.32**
- For doors over 1600 mm (63") it is suggested to use two SMOVE, one to be inserted into the upper part and the second into the lower part of the cabinet side opposite the hinges



For recess mounting



For surface mounting



SMOVE

- Light resistance
- With pre-attached grommet
- Mount into the cabinet side opposite the hinges
- For optimal performance, we suggest mounting in the center of the side panel
- To be used for doors from 450 mm (17 23/32") to 600 mm (23 5/8")

Material: Plastic

Color	Model	Item No.
beige	D005SNB	356.11.400
light brown	D005SNQ	356.11.100

SMOVE

- Medium resistance
- With pre-attached grommet
- Mount approximately into the center of the top or the base panel of the cabinet
- It is suggested to use the test block to verify the optimum positioning of this SMOVE before assembly

Material: Plastic

Color	Model	Item No.
beige	D006SNB	356.11.410
light brown	D006SNQ	356.11.110

SMOVE

- Heavy resistance
- With pre-attached grommet
- Mount into the top or the base panel of the cabinet on the hinged side
- A drilling distance of 27 mm (1 1/16") from the cabinet side is suggested

Material: Plastic

Color	Model	Item No.
beige	D008SNB	356.11.420
light brown	D008SNQ	356.11.120

10 mm twist drill bit HSS

Material: Steel

Item No.
001.41.293

Packing: 10 pcs.

Dimensional data not binding. We reserve the right to alter specifications without notice.